

FL # FL4138-R1 Application Type Revision Code Version 2004 Application Status Approved

Comments Archived  Product Manufacturer Mesker Door, Inc. Address/Phone/Email 3440 Stanwood Blvd.

Huntsville, AL 35811  
(256) 851-6670

rickw@rwbgconsultants.com Authorized Signature Stephen Frates

rickw@rwbgconsultants.com Technical Representative Address/Phone/Email Quality Assurance Representative Address/Phone/Email Category Exterior Doors Subcategory Swinging Exterior Door Assemblies Compliance Method Evaluation Report from a Florida Registered Architect or a Licensed Florida Professional Engineer

Evaluation Report - Hardcopy Received Florida Engineer or Architect Name who developed the Evaluation Report Wendell W. HANEY Florida License PE-54158 Quality Assurance Entity Underwriters Laboratories Inc. Quality Assurance Contract Expiration Date

Validated By L.F. Schmidt, P.E.  Validation Checklist - Hardcopy Received Certificate of Independence Referenced Standard and Year (of Standard)

<b>Standard</b>	<b>Year</b>
Accepted Engineering Practice	2004
TAS 201 and TAS 203	1994
TAS 202	1994

Equivalence of Product Standards

Certified By

Sections from the Code Product Approval Method Method 1 Option D Date Submitted 09/12/2005 Date Validated 09/23/2005 Date Pending FBC Approval 09/27/2005 Date Approved 10/17/2005

### Summary of Products

FL #	Model, Number or Name	Description
4138.1	a. "H Door" - Commercial Steel Single Door	3'0 x 7'0 - Outswing 16 Ga. Steel Door in a Hollow Metal Frame
<b>Limits of Use (See Other)</b> <b>Approved for use in HVHZ:</b> <b>Approved for use outside HVHZ:</b> <b>Impact Resistant:</b> <b>Design Pressure: +/-</b> <b>Other:</b> This product meets the requirements for the State of Florida excluding the "HVHZ". When used in wind-borne debris regions this product complies with Section 1609.1.4 of the Florida Building Code as an impact resistant product and does not require the use of an external impact resistant covering. Maximum Design Pressure Rating		<b>Installation Instructions</b> Verified By: Created by Independent Third Party: <b>Evaluation Reports</b> <a href="#">PTID 4138 R1 T 4138.1 EVAL.pdf</a> <a href="#">PTID 4138 R1 T 4138.1 INST.pdf</a> <a href="#">PTID 4138 R1 T 4138.2 EVAL.pdf</a> <a href="#">PTID 4138 R1 T 4138.2 INST.pdf</a> Created by Independent Third Party:

<p>Positive 116.0 PSF and Negative 116.0 PSF (see 4138.1 EVAL for any additional size and use limitations).</p>	
<p>4138.2</p>	<p>b. "H Door" - Commercial Steel Double Door</p> <p>6'0 x 7'0 - Outswing 16 Ga. Steel Door in a Hollow Metal Frame</p>
<p><b>Limits of Use</b> (See Other)  <b>Approved for use in HVHZ:</b>  <b>Approved for use outside HVHZ:</b>  <b>Impact Resistant:</b>  <b>Design Pressure:</b> +/-  <b>Other:</b> This product meets the requirements for the State of Florida excluding the "HVHZ". When used in wind-borne debris regions this product complies with Section 1609.1.4 of the Florida Building Code as an impact resistant product and does not require the use of an external impact resistant covering. Maximum Design Pressure Rating – Positive 80.0 PSF and Negative 80.0 PSF (see 4138.2 EVAL for any additional size and use limitations).</p>	<p><b>Installation Instructions</b>  Verified By:  Created by Independent Third Party:  <b>Evaluation Reports</b>  Created by Independent Third Party:</p>